

## ALPHA 4034

### Acrylic Roof Coating

UPDATED 9/4/16

**Product Overview:** ALPHA 4034 is a water-based acrylic roof coating that is designed to protect and maintain existing roof surfaces. Once cured, this material reflects heat and light to provide a cooler roof. It also adds durability and UV light resistance, as well as low temperature flexibility. ALPHA 4034 exhibits self-compatibility, and can thus be re-coated as often as needed.

**Product Uses:** ALPHA 4034 can be applied to a wide variety of roofing surfaces. It actively bonds to: polyurethane foam, aluminum, galvanized steel, fiberglass, and cured concrete. It can also be applied to EPDM membrane, provided that the rubber has first been cleaned and primed.

#### Technical Information:

<b>Raw Material Base</b> .....Water, Latex Emulsion	<b>Odor</b> .....Odorless
<b>Color</b> ..... White	<b>Coverage</b> .....200 ft <sup>2</sup> per gallon @ 8 mil
<b>Specific Gravity</b> .....1.40 – 1.50	<b>Service Temp. Range</b> .....-40° – 180°F
<b>Solids</b> .....66%	<b>Application Temp. Range</b> .....33° – 120°F
<b>Viscosity</b> ..... 10,000 – 15,000 cps	<b>Manufactured State</b> .....5, 1, ¼ gallon pails
<b>QUV Exposure</b> .....No Change after 1 Year	<b>Shelf Life</b> .....12 Months

**Application Information:** Ensure substrates are clean, dry, and free of oil and moisture. Exercise care during application to prevent air or contaminant entrapment. This product can be applied by brush or roller. A skin begins to form 20 minutes after application, and a full cure is achieved within 4-6 hours, depending on coat thickness.

**Safety Instructions:** No special requirements are needed. Consult the product SDS for detailed safety information.

**Contact Us:** For more information regarding this product and others, please contact us at:

Alpha Systems LLC  
5120 Beck Drive  
Elkhart, IN 46516

Phone: 1-574-295-5206  
Fax: 1-574-970-2703  
[www.alphallc.us](http://www.alphallc.us)

RESIDENTIAL HOUSING · RVS/UTILITY TRAILER · HVAC ·  
COMMERCIAL/INDUSTRIAL ROOFING · MARINE · MOBILE/MODULAR · METAL BUILDING

**Disclaimer:** The information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Alpha Systems control are such that Alpha Systems assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.