



## ALPHA Q202

### Mylar-Backed Butyl Tape

UPDATED 8/23/16

**Product Overview:** ALPHA Q202 is a specialized butyl PSA tape designed to provide weatherproofing characteristics and structural support when used to seal corner joint applications. The composition of ALPHA Q202 consists of a 1.4 mil transparent Mylar facer that is permanently anchored to 30 mils of butyl adhesive. This adhesive is a non-drying compound that features excellent resistance to water, weather, and air intrusion and adheres well to all non-porous substrates.

**Product Uses:** ALPHA Q202 is ideally suited to seal the joints of flat, even surfaces, most notably the corners of RV units that use laminated sidewalls. ALPHA Q202 is also used in the marine, HVAC, and metal building industries. It is available in .75", 1.25", 1.5", 1.75", and 2" widths.

#### Technical Information:

|                                     |                            |                                      |                        |
|-------------------------------------|----------------------------|--------------------------------------|------------------------|
| <b>Raw Material Base</b> .....      | Rubber Based Mastic        | <b>Odor</b> .....                    | Odorless               |
| <b>Cone Penetration</b> .....       | 10.5 – 11.5 mm (77°F)      | <b>Tensile Strength</b> .....        | 12 – 14 PSI (ADH only) |
| <b>Color</b> .....                  | (ADH) White, (FACER) Clear | <b>Service Temp. Range</b> .....     | -40° – 180°F           |
| <b>Specific Gravity</b> .....       | 1.55 – 1.65                | <b>Application Temp. Range</b> ..... | -5° – 120°F            |
| <b>Solids</b> .....                 | 100%                       | <b>Physical State</b> .....          | Solid                  |
| <b>Elongation (ASTM D412)</b> ..... | >800% (ADH only)           | <b>Manufactured State</b> .....      | PSA Tape Rolls         |
| <b>QUV Exposure</b> .....           | No Change after 100 days   | <b>Shelf Life</b> .....              | 12 Months              |

**Application Information:** ALPHA Q202 material is extruded onto a permanent Mylar facer. For most efficient usage, guide the tape into place by hand on one surface and press or roll to activate the adhesive and eliminate wrinkles. Once anchored to the first surface, repeat this process for the second surface, if applicable. Use scissors to cleanly terminate tape applications.

**Safety Instructions:** No special requirements are needed. Consult the product SDS for detailed safety information.

**Contact Us:** For more information regarding this product and others, please contact us at:

Alpha Systems LLC  
5120 Beck Drive  
Elkhart, IN 46516

Phone: 1-574-295-5206  
Fax: 1-574-970-2703  
[www.alphallc.us](http://www.alphallc.us)

RESIDENTIAL HOUSING · RVS/UTILITY TRAILER · HVAC ·  
COMMERCIAL/INDUSTRIAL ROOFING · MARINE · MOBILE/MODULAR · METAL BUILDING

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Alpha Systems control are such that Alpha Systems assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.