
TECHNICAL DATA SHEET

TUFF-PLY FLOORING SYSTEM

TUFF-PLY FLOORING is a state-of-the-art technologically advanced TPO (thermoplastic polyolefin) flooring membrane. TUFF-PLY FLOORING is designed for use as a durable flooring membrane in today's recreational vehicles, cargo trailers, toy haulers and ramp doors.

The advanced polymer utilized in the compounding of TUFF-PLY FLOORING delivers the unique "double feature" benefits of outstanding durability combined with unmatched traction, even when wet!

TUFF-PLY FLOORING incorporates a spun polyester (fleece) backing, which is mechanically attached during the extrusion manufacturing process. This backing enables TUFF-PLY FLOORING to be easily bonded to a variety of porous wood surfaces. Alpha Systems 3080 TPO Flooring Adhesive is recommended for bonding TUFF-PLY FLOORING.

***TUFF-PLY FLOORING is available in three surface textures:**

Levant, Diamond Plate & Nickel Plate patterns.

***TUFF-PLY FLOORING is available in two thicknesses: 0.050" and 0.100".**

***Current roll packaging: 102" x 150' x (0.050" or 0.100").**

***Available colors: Charcoal or Grey**



Levant



Diamond Plate



Nickel Plate

Installation Instructions:

ALPHA SYSTEMS 3080 May be applied with brush, roller or trowel. Surface should be free of dirt, oil, or other contaminants. Apply a coat of adhesive to one surface (16-20 mils thick). Mate the two surfaces as soon as possible (approx. open time 5-10 minutes). Use a 70 lb linoleum roller (or equivalent) to apply pressure so that adhesive can properly penetrate into the fleece. **IMMEDIATELY following the adhesive application and rolling process mechanically fasten the perimeter of the TUFF-PLY FLOORING.**